

# ABC

## dive shop

**OCEANIC DELTA 5 WHITE + EDX DIN  
SET INCL OCTOPUS + BAG**

**€699,00 - €879,00**

Set

**First Stage EDX**

**Second Stage Delta 5 White**

**Octopus Alpha 10**

**Regulator Bag**



---

**SKU:** SARQ13111200-1-1-1

**Category:** [Automatenset compleet](#)

**Tag:** [Oceanic](#)

**GALLERY IMAGES**

# ARV



## PRODUCT DESCRIPTION

The Delta 5 is the next step in a long line of remarkably reliable, durable and smoothly breathing regulators to carry that name. Sure, we've given it an updated look, but that's not all. Like the deltas before it the 5 comes standard with our patented Dynamic Adjustment Technology that, once set by the diver, provides consistent airflow at any depth. It also comes standard with a dive/pre-dive switch and a



super comfortable orthodontic mouth piece. This latest edition though has an updated, all metal pneumatic valve providing super smooth breathing performance in any condition.

## **READY FOR ANYTHING**

Over 20 years ago we gave ourselves a challenge to design a rugged and reliable all-purpose regulator that would be at home in cold water or warm and breathe just as good at 30 feet as it did at 130. We called that regulator the Delta, and we still do.

The Delta5 is the next step in a long line of remarkably reliable, durable and smoothly breathing regulators to carry that name. Sure, we've given it an updated look, but that's not all. Like the Delta's before it, the 5 comes standard with our patented Dynamic Adjustment Technology that, once set by the diver, provides consistent airflow at any depth. They also come standard with a dive/pre-dive switch and a super comfortable orthodontic mouthpiece. This latest edition though has an updated, all metal pneumatic valve providing super smooth breathing performance in any condition. We have also added a heat exchanger, positioned on the hose connection to the 2nd stage, to further increase its already stellar cold water performance.

We've paired the Delta5 with the new eDX. This top-of-the-line cold forged, over-balanced diaphragm first stage is environmentally sealed and comes with 4 low-pressure and 2 high-pressure ports. It also comes equipped with a heat exchanger for added cold water performance.

- Pneumatically balanced all-metal valve.
- Dive/pre-dive switch & patented dynamic airflow adjustment control.
- Mechanical Purge button for consistent air-flow pressure on during purge.
- Nitrox Compatibility - Standard to 40%.
- Balanced diaphragm first stage eDX is environmentally sealed and cold-water ready.
- Heat Exchanger for Improved cold-water performance.
- Ergonomic exhalation venting.
- Dimensions (Front Profile) - 2.5 inch diameter (circular).
- Dual-material orthodontic mouthpiece with bite tabs.
- Service Interval - 2 Year, Required.
- Lifetime Warranty with Free Parts for Life.
- 30 day satisfaction guarantee.
- Miflex Braided Hose - Supplied with complete models only.
- Optional Universal Swivel Adapter - the optional Universal Swivel comes separate but can be easily installed with an adjustable torque wrench and 5 min of free time. Instructions are provided.

**DELTA 5** 2nd stage Available in Black & White



Adjustments	Dive/pre-dive switch & Patented Dynamic airflow Adjustment control
Valve Type	Pneumatically balanced all-metal valve
Heat Exchanger	For enhanced cold-water performance
Mouthpiece Type	Orthodontic w/ Bite Tabs
Nitrox Compatibility	Standard to 40%
Swivel Adapter	Optional
Dimensions Front Profile	2.5 inch diameter circular
Warranty	Lifetime & Free Parts for Life
Service Interval	2 Year, Required
Satisfaction Guarantee	30 Days

#### **eDX Specs 1st stage**

Valve Type	Over-Balanced Diaphragm
Pressure Ports	LP 4, HP 2
Nitrox Compatibility	Standard to 40%
Environmental Protection	Sealed Valve Design
Warranty	Lifetime & Free Parts for Life
Service Interval	2 Year, Required
Satisfaction Guarantee	30 Days

#### **Octopus Alpha 10**

- The best price-to-performance ratio in its class
- Designed to perform to the U.S. Navy's Class A standards
- Inexpensive to maintain
- Available with Miflex® Hose
- Pneumatically balanced demand valve
- Integrated Purge Button
- Orthodontic Mouthpiece
- Nitrox Compatibility - Standard to 40%

- Weight (without hose) – 6 ounces
- Dimensions (front profile) – 2.9 inches



## ADDITIONAL INFORMATION

### kies soort manometer

Geen manometer, Manometer ESM + infl slang, Suunto CB-One/300 + infl slang, Suunto CB-One + kompass + infl slang